

SERIES
AIR CENTRE 7,5 - 15 kW

ROTARY VANE COMPRESSORS

AC
ACS
AC PLUS
ACS PLUS



SERIES AIR CENTRE

About us



Ing. **Enea Mattei SpA** is an Italian company that has been producing air compressors since 1919. Over the years, the company has continually evolved and is today one of the world's foremost companies in the compressed air sector and the leader in the production of rotary vane compressors.

Behind the success of Mattei are the choices the company has made in terms of design, production and marketing, driven by the results of its continual and in-depth research and development programmes.

During these years of continual change, Mattei has been able to adapt to the requirements of the market and through the results of its research has created products that are always innovative and technologically advanced.



Certified quality

Quality as an integral part of all company functions and constant improvement of all production processes so as to always guarantee the maximum level of reliability and satisfaction. This, in brief, is the value and the meaning of **Mattei's** operational philosophy. A way of approaching the market and customers that makes **Mattei** an absolute point of reference in the compressed air sector.

Since 1994, **Mattei** has been operating with a Quality System certified by the DNV Institute under UNI EN ISO 9001 regulations.





Rotary vane compressors

Series AIR CENTRE

Mattei's Air Centre series compressors are complete and efficient machines that are ideal for any type of industrial application.

Direct coupling

Mattei has always produced compressors in which the electric motor, which turns at a speed of only 1,500 rpm, is directly coupled to the compression unit by means of a flexible joint. This direct, in-line coupling results in considerable energy saving as there are no losses due to the presence of pulley wheels and drive belts.



Automatic flow rate control

As well as the classic "ON/OFF OPERATION" mode, all of the models, from the AC 4 to the AC 15s, are fitted with the special modulating proportional intake valve which allows air supply at a constant pressure and even offers the possibility of working without an air storage tank.



A high efficiency oil separation

The separation of the lubrication oil from the compressed air takes place in multiple stages. A first separation occurs in the oil chamber as the air passes through a labyrinth path, then it continues at the separator inlet (before the filter) where the air flow slows down passing through a series of directional variations, and finally through the coalescing filter. Due to this superior separation system the oil carry over is extremely low, leading to improved separator life, greater protection for the application and reduced operating costs.

Compressor and dryer: all - in - one

The plus version includes the integrated installation of a direct expansion refrigeration dryer, which is air cooled and filled with environmentally friendly gas. The combination of a Mattei rotary vane air compressor with an integrated dryer and where applicable mounted on an air receiver is the ideal solution for a complete and compact system.

Durable and quiet

AIR CENTRE compressors are epoxy powder coated and corrosion and scratch resistant. In addition they are lined internally with a thick layer of high-quality soundproof material and equipped with a high efficiency cabinet pre-filter. This filtering device prevents the radiator and main air filter from premature clogging caused by impurities in the intake air, thus providing additional cost savings.

MAESTRO^{XS}

to have everything under control

With a view to energy saving, the communication inside a compressor room plays a decisive role.

It is absolutely essential to manage, control and immediately intervene in the operation of the system in order to prevent waste and unnecessary energy consumption. For this reason, all of Mattei's Air Centre compressors are fitted as standard with a microprocessor command and control device: Maestro^{XS}.

Maestro^{XS} is programmable controller, which regulate the compressor's operation and adapt this to the specific requirements of the air distribution system. It has different programming levels and special options of controlling and analysing the operation and faults. Advanced programming and analysis levels are protected by digital codes to avoid unintentional tampering.

Maestro^{XS} has an integrated memory module that stores the operational settings and data in case of a power failure.



MAESTRO^{XS}: features and functions

- Ergonomic control panel with quick access keys to main menus.
- Menus access keys, start, stop and reset led keys.
- Semi-graphic LCD display with illuminated text.
- 24 Vdc digital inputs.
- Digital dry contacts output up to 230 Vac and up to 24 Vdc.
- Interfaces:
 - RS485 for intercommunication with other MAESTRO devices.
 - RS485 (optional) to communicate with the supervising PC and network.
- Analogue data display (line pressure, chamber pressure, oil temperature, outgoing air temperature) and general data (alarms, operating messages, machine state, maximum and minimum pressure, last start and stop times).
- Hour counter to display the enabled, working and load times and maintenance notices.
- Events database to store alarms and blocks, with alarm intervention indication, alarm intervention time, machine state.
- Multi-language user interface.
- Weekly and hourly programmable start and stop times.
- Immediate reading of the compressor operating data on the display.
- Basic and advanced parameters programming for an optimal operation of the compressor.
- Storage of up to 20 malfunctioning events.
- Storage of the last 20 programme modifications.
- Control of the integrated dryer.
- Machine start and stop remote control.
- The feedback (as standard), through dry contacts, of the following machine states: enabled compressor, working compressor, loaded compressor, blocked compressor.



Technical data

50 Hz

 Model	 Tension	 Air receiver	 Power								 Sound pressure level							 Weight	
					8 bar 115 psig L		10 bar 150 psig H		13 bar 175 psig HH			Length		Width		Height			
	V/f	I	kW	hp	m³/min	cfm	m³/min	cfm	m³/min	cfm	dB(A)	mm	inch	mm	inch	mm	inch	kg	lbs
AC 7	400/3	-	7,5	10	1,38	48,7	1,15	40,6	0,96	33,9	65	1250	49,3	610	24	1040	41	220	484
AC 11	400/3	-	11	15	1,97	69,6	1,7	60	1,35	47,7	65	1250	49,3	610	24	1040	41	240	528
AC 15s	400/3	-	15	20	-	-	1,95	68,9	1,83	64,6	65	1250	49,3	610	24	1040	41	260	572
AC 7 PLUS	400/3	-	7,5	10	1,38	48,7	1,15	40,6	0,96	33,9	65	1250	49,3	610	24	1040	41	245	539
AC 11 PLUS	400/3	-	11	15	1,97	69,6	1,7	60	1,35	47,7	65	1250	49,3	610	24	1040	41	265	583
AC 15s PLUS	400/3	-	15	20	-	-	1,95	68,9	1,83	64,6	65	1250	49,3	610	24	1040	41	285	627
ACS 7	400/3	270	7,5	10	1,38	48,7	1,15	40,6	0,96	33,9	65	1480	58,3	750	29,6	1550	61	310	682
ACS 11	400/3	270	11	15	1,97	69,6	1,7	60	1,35	47,7	65	1480	58,3	750	29,6	1550	61	330	726
ACS 15s	400/3	270	15	20	-	-	1,95	68,9	1,83	64,6	65	1480	58,3	750	29,6	1550	61	350	770
ACS 7 PLUS	400/3	270	7,5	10	1,38	48,7	1,15	40,6	0,96	33,9	65	1480	58,3	750	29,6	1550	61	335	737
ACS 11 PLUS	400/3	270	11	15	1,97	69,6	1,7	60	1,35	47,7	65	1480	58,3	750	29,6	1550	61	355	781
ACS 15s PLUS	400/3	270	15	20	-	-	1,95	68,9	1,83	64,6	65	1480	58,3	750	29,6	1550	61	375	825

60 Hz

																			
					8 bar 115 psig L		10 bar 150 psig H		13 bar 175 psig HH			Length		Width		Height			
Model	Tension	Air receiver	kW	hp	m³/min	cfm	m³/min	cfm	m³/min	cfm	dB(A)	mm	inch	mm	inch	mm	inch	kg	lbs
AC 7	460/3	-	7,5	10	1,39	49,1	1,2	42,4	1,18	41,7	67	1250	49,3	610	24	1040	41	220	484
AC 11	460/3	-	11	15	2,11	74,5	1,87	66	1,65	58,3	67	1250	49,3	610	24	1040	41	240	528
AC 7 PLUS	460/3	-	7,5	10	1,39	49,1	1,2	42,4	1,18	41,7	67	1250	49,3	610	24	1040	41	245	539
AC 11 PLUS	460/3	-	11	15	2,11	74,5	1,87	66	1,65	58,3	67	1250	49,3	610	24	1040	41	265	583
ACS 7	460/3	270	7,5	10	1,39	49,1	1,2	42,4	1,18	41,7	67	1480	58,3	750	29,6	1550	61	310	682
ACS 11	460/3	270	11	15	2,11	74,5	1,87	66	1,65	58,3	67	1480	58,3	750	29,6	1550	61	330	726
ACS 7 PLUS	460/3	270	7,5	10	1,39	49,1	1,2	42,4	1,18	41,7	67	1480	58,3	750	29,6	1550	61	335	737
ACS 11 PLUS	460/3	270	11	15	2,11	74,5	1,87	66	1,65	58,3	67	1480	58,3	750	29,6	1550	61	355	781

F.A.D. in accordance with ISO 1217, annex "C" | Sound pressure level according to ISO 2151, tolerance ± 3 dB(A) | Working pressure: 7,5 bar for version 8 bar - 9,5 bar for version 10 bar - 12,5 bar for version 13 bar



ITALY - ING. ENEA MATTEI SpA
Strada Padana Superiore, 307
20090 VIMODRONE (MI)
Tel + 39 02253051 - Fax +39 0225305243
E-mail: info@mattei.it

www.matteigroup.com

FRANCE

MATTEI COMPRESSEURS
Phone +33 535 542 205 - Fax +33 972 316 833
E-MAIL: infos@mattei.fr - www.mattei.fr

GERMANY

MATTEI KOMPRESSOREN DEUTSCHLAND GmbH
Phone +49 7151 5002560 - Fax +49 7151 5002565
E-MAIL: info@mattei-kompressoren.de - www.mattei-kompressoren.de

GREAT BRITAIN

MATTEI COMPRESSORS Ltd
Phone +44 (0)1789 450577 - Fax +44 (0)1789 450698
E-MAIL: info@mattei.co.uk - www.mattei.co.uk

U.S.A.

MATTEI COMPRESSORS Inc
Phone +1 410 5217020 - Fax +1 410 5217024
E-MAIL: info@matteicomp.com - www.matteicomp.com

RUSSIAN FEDERATION

ING. ENEA MATTEI SpA
Phone +7-495-739 41 90 - Fax +7-495-739 41 90
E-MAIL: mattei@inbox.ru

SPAIN

ING. ENEA MATTEI SpA
Phone +34 93 435 03 94 - Fax +34 93 455 26 76
E-MAIL: info@mattei.it

PEOPLE'S REPUBLIC OF CHINA

Mattei (SuZhou) Air Compressors Manufacturing Co., Ltd
WFOE by Ing. Enea Mattei SpA - Italy
Tel: +86 512 66679986 Fax: +86 512 66679989
E-MAIL: info@matteisuzhou.cn - www.matteisuzhou.com

UNI EN ISO 9001:2008

TUNGS-STAR SRL

Gascompression Division



0266-214.463



0742-270.201



compression@tungs-star.ro



Romania, jud. Harghita
Odorheiu Secuiesc
str. Budvár nr. 31